



# Specification - Com Lite 3cct Backlit Panels

Revision 1



Product Information				
Model No.	SBP20MC	SBP36MC	SBP362MC	BP60MC
Power Consumption(±5%)	18w	36w	37w	60w
Power Supply	Lifud			
Input Voltage	220-240 VAC, 50-60Hz			
Power Factor	>0.90			
Driver Type	Constant Current			
LED Type	SMD led			
Luminous Flux (±10%) 3000k Ra80	1810lm	3920lm	3445lm	6490lm
Luminous Flux (±10%) 4000k Ra80	2110lm	4250lm	3765lm	6865lm
Efficiency (4000k)	> 115lm per watt	> 125lm per watt	> 105lm per watt	> 120lm per watt
CCT	3000k, 4000k, 5700k selectable			
Colour Rendering Index	Ra80			
Beam Angle	90 degrees			
Class	Class II			
SCDM	< 6			
IK rating	IK06			
IP Rating	IP44			
Colour	White			
Diffuser Material	pmma			
Dimensions	595x295x28mm	595x595x28mm	1195x295x28mm	1195x595x28mm

Options	
Dimmable	Dali, DSI, 1-10v, Triac
Emergency	Standard, self test, Dali self test
Sensor	Remote sensor only

## Applications

Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail



## Accessories

<b>Surface Mount Frame</b>	PSF600/300BL	PSF600/600BL	PSF1200/300BL	PSF1200/600BL
<b>Recessed Mount Frame</b>	PRF600/300	PRF600/600	PRF1200/300	PRF1200/600
<b>Suspension Kits</b>	SUSKIT/3M (4 wire 3mtr suspension kit)			
	SUSKIT/5M (4 wire 5mtr suspension kit)			
	SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)			
<b>Plasterboard Clips</b>	LEDP/PBC (set of 4)			

## Lifespan and Warranty

<b>Lifetime of LED @ Ta=25°C</b>	> 50,000hrs L80B20
<b>Warranty</b>	5 years