

Specification - Com Lite BH Models

Revision 1



Product Information

Model No.	BH15MC
Power Consumption(±5%)	13w
Power Supply	Lifud
Input Voltage	220-240 VAC, 50-60Hz
Power Factor	>0.90
Driver Type	Constant Current
LED Type	SMD led
Colour	RAL9016
Luminous Flux (±10%) 4000k Ra80	1210lm
Efficiency (4000k)	> 85lm per watt
CCT	3000/4000/6000k selectable
Colour Rendering Index	Ra80
Beam Angle	120 degrees
Class	Class I
SCDM	< 6
IK rating	IK08
IP Rating	IP54
Colour	White
Diffuser Material	Polycarbonate
Body Material	Polycarbonate
Dimensions (Diax Depth)	320x90mm
Operating Temperature	-20°C ~45°C

Options

Dimmable	Dali, DSI, 1-10v, Triac
Emergency	Standard, self test, Dali self test
Sensor	Inbuilt microwave or photocell

Applications

Corridors, Hotels, Reception Area's, Stairwells



Accessories

Polished Chrome Ring	CR/RING
-----------------------------	---------

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 50,000hrs L80B50
----------------------------------	--------------------

Warranty	3 years (5 year option)
-----------------	-------------------------