

Specification - Com Lite Slim BH and CBH Models

Revision 1



Product Information						
Model No.	BH15WB/4	BH15BKPIR/4	BH15WHPIR/4	CBH15WB/4	CBH15BKPIR/4	CBH15WHPIR/4
Description	Rectangular with black/white ring	Rectangular Black with PIR	Rectangular White with PIR	Circular with black/white ring	Circular Black with PIR	Circular White with PIR
Power Consumption(±5%)	15w	15w	15w	15w	15w	15w
Input Voltage	220-240 VAC, 50-60Hz					
Power Factor	>0.90					
Driver Type	Constant Current					
LED Type	SMD led					
Luminous Flux (±10%) 4000k Ra80	1100lm	1100lm	1100lm	1100lm	1100lm	1100lm
Efficiency (4000k)	> 70lm per watt					
CCT	4000k					
Colour Rendering Index	Ra80					
Beam Angle	100 degrees					
Class	Class I					
SCDM	< 6					
IK rating	IK08					
IP Rating	IP54					
Colour	Black and White					
Diffuser Material	Polycarbonate					
Body Material	Polycarbonate					
Dimensions	212x120x45mm	212x120x45mm	212x120x45mm	210x49mm	210x49mm	210x49mm
Operating Temperature	-20°C ~45°C					
Options						
Dimmable	Not available					
Emergency	Not available					
Sensor	Not available					
Applications						
Corridors, Residential complexes, Stairwells						
Lifespan and Warranty						
Lifetime of LED @ Ta=25°C	> 30,000hrs L70B50					
Warranty	3 years					