COM LITE BULKHEADS SLIM BH AND CBH











KEY FEATURES

- 30,000hr life expectancy
- CRI > 80
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Sensor versions are fully adjustable up to 5mins max
- Sensor versions have detection distance of 9mtrs and 140 degree detection
- Zero maintenance

MATERIALS

- High output led chip used
- Reliable inbuilt driver
- Durable polycarbonate base and cover

ADDITIONAL INFORMATION

4000k supplied as standard

WARRANTY

3 years

IP54



PRODUCT CODE RECTANGULAR	DESCRIPTION	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
BH15WB/4	Rectangular bulkhead 15W 4000k with Black and White trims	15W	212 x 45 x 120	SMD LED	1100lm	> 70
BH15BKPIR/4	Rectangular bulkhead 15W 4000k Black trim and inbuilt PIR	15W	212 x 45 x 120	SMD LED	1100lm	> 70
BH15WHPIR/4	Rectangular bulkhead 15W 4000k White trim and inbuilt PIR	15W	212 x 45 x 120	SMD LED	1100lm	> 70

PRODUCT CODE CIRCULAR	DESCRIPTION	WATTAGE (W)	SIZE Dia x W (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
CBH15WB/4	Circular bulkhead 15W 4000k with Black and White trims	15W	210 x 49	SMD LED	1100lm	> 70
CBH15BKPIR/4	Circular bulkhead 15W 4000k Black trim and inbuilt PIR	15W	210 x 49	SMD LED	1100lm	> 70
CBH15WHPIR/4	Circular bulkhead 15W 4000k White trim and inbuilt PIR	15W	210 x 49	SMD LED	1100lm	> 70









