

# Specification - Com Lite CLD Models

Revision 1



## Product Information

Model No.	CLD13LG	CLD25LG/MC	CLD35LG/MC
Power Consumption(±5%)	13w	25w	35w
Power Supply	Lifud or other premium brand		
Input Voltage	220-240 VAC, 50-60Hz		
Power Factor	>0.90		
Driver Type	Constant Current		
LED Type	SMD		
Luminous Flux (±10%) 3000k Ra80	1025lm	2380lm	3400lm
Luminous Flux (±10%) 4000k Ra80	1170lm	2535lm	3800lm
Efficiency (4000k)	>80lm per watt	>95lm per watt	>95lm per watt
CCT	4000K		
Colour Rendering Index	Ra80		
Beam Angle	65 degrees		
Class	Class I		
SCDM	< 6		
IK rating	IK06		
IP Rating	IP44		
Cut Out	90-100mm	160-180mm	200-220mm
Dimensions (Dia x Height)	110x80mm	190x100mm	230x110mm

## Options

Dimmable	Dali, DSI, 1-10v
Emergency	Standard, self test, Dali self test

## Applications

Carehomes, Domestic Applications, Hotels, Offices, Retail

## Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20
Warranty	5 years