



COM LITE DOWNLIGHTS: CLD MODELS



Com Lite
Commercial Lighting

A range of stylish downlights with a microprism diffuser to reduce glare. These downlights are both aesthetically pleasing and energy saving providing the user with a perfect solution for modernisation. They are available in a range of sizes and wattages. They are suitable for office, retail and residential areas.



KEY FEATURES

- 40,000hr life expectancy
- CRI > 80
- Ideal for use in boardrooms, carehomes, residential, retail and showrooms
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Zero maintenance

MATERIALS

- Complete with LED lightsource
- Die cast aluminium heat sink for optimum performance
- Microprism diffuser
- Reliable driver supplied with option to upgrade to European brand

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

3 years as standard with 5 year option

IP RATING

IP44

PRODUCT CODE	COLOUR RENDERING	WATTAGE (W)	DIMENSIONS Dia x Depth (mm)	CUT OUT (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
CLD13LG/3	3000k	12W	110 x 80	90-100	SMD LED	1080lm	> 90
CLD13LG/4	4000k	12W	110 x 80	90-100	SMD LED	1210lm	> 100
CLD25LG/3	3000k	24W	190 x 100	160-180	SMD LED	2380lm	> 95
CLD25LG/4	4000k	24W	190 x 100	160-180	SMD LED	2510lm	> 105
CLD35LG/3	3000k	34W	230 x 110	200-220	SMD LED	3200lm	> 90
CLD35LG/4	4000k	34W	230 x 110	200-220	SMD LED	3630lm	> 105