

COM LITE DOWNLIGHTS: CLGD MODELS



A range of stylish low glare downlights. These downlights are both aesthetically pleasing and energy saving providing the user with a perfect solution for modernisation. They are available in a couple of sizes and wattages and all are 3CCT as standard. They are suitable for office, retail and residential areas.



KEY FEATURES

- 3CCT as standard 2700/4000/5700k
- 40,000hr life expectancy
- CRI > 80
- Ideal for use in boardrooms, carehomes, residential, retail and showrooms
- Manufactured with quality materials and reliable driver
- PF > 0.90
- UGR < 19
- Zero maintenance

MATERIALS

- Complete with LED lightsource
- Iron bezel, aluminium reflector and polycarbonate housing
- Reliable driver supplied with option to upgrade to European brand

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

3 years as standard with 5 year option

IP RATING

IP44

PRODUCT CODE	WATTAGE (W)	DIMENSIONS Dia x Depth (mm)	CUT OUT (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
CLGD13MC	13W	145 x 82	125-135	SMD LED	1080/1200/1210lm	> 80
CLGD18MC	18W	228 x 98	200-210	SMD LED	1820/1900/1960lm	> 100
CLGD13MCD	13W	145 x 82	125-135	SMD LED	1080/1200/1210lm	> 80
CLGD18MCD	18W	228 x 98	200-210	SMD LED	1820/1900/1960lm	> 100