


Specification - Com Lite Floods V1 3CCT Models

Revision 1



Product Information						
Model No.	DFL30MC	DFL50MC	DFL100MC	DFL150MC	DFL200MC	DFL300MC
Power Consumption(±5%)	30w	50w	100w	150w	200w	300w
Power Supply	Done for 30-50w /Sosen for 100w Upwards					
Input Voltage	220-240 VAC, 50-60Hz					
Power Factor	>0.90					
Driver Type	Constant Current					
LED Type	SMD					
Luminous Flux (±10%) 4000k Ra80	4050lm	6150lm	13085lm	20085lm	26740lm	41510lm
Optic	Symmetrical beam					
Efficiency (4000k)	> 125lm per watt					
CCT	3000k/4000k/5700k					
Colour Rendering Index	Ra80					
Surge Protection	10KV SPD (100w upwards)					
Class	Class I					
SCDM	< 6					
IK rating	IK08					
IP Rating	IP66					
Colour	Black					
Category of Corrosion	C3					
Options						
Dimmable	Dali, DSI, 1-10v					
Emergency	Standard, self test, Dali self test (Remote)					
Applications						
Carparks, Hotels, Retail, Sports Courts and Fields, Warehouses						

Beam Angle



Lifespan and Warranty

Lifetime of LED @ Ta=25°C > 50,000hrs L80B20

Warranty 5 years

Dimensions

