

COM LITE FLOODS V1



Com Lite
Commercial Lighting

Com Lite V1 models are a range of high end, durable and efficient floodlights designed to be versatile, easy to install and reliable, manufactured only with quality components. They are suitable for large open areas like car parks, yards and external walkways.



KEY FEATURES

- 50,000hr life expectancy
- > 125lm per watt
- CRI > 80
- Ideal for use in car parks, garages, parks, yards and walkways
- IP66 rated
- Large choice of accessories, beam angles and asymmetric lens
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Preflexed for ease of installation
- Suitable for pole and wall mounting
- Zero maintenance

MATERIALS

- Complete with SMD LED lightsource
- High quality heat sink made with aluminium alloy
- Glass diffuser

ACCESSORIES AVAILABLE

- Asymmetric lens available for different beam angles
- Various beam angles available
- Various pole mounting brackets available

ADDITIONAL INFORMATION

- 6000k and 4000k available
- Working temperature -30 to +50 degrees

DIMMABLE OPTIONS


- /DD for DSI digital dimmable (on selected models)
- /DL for Dali and switch dimmable (on selected models)

WARRANTY


5 years

IP RATING

IP66



DFL200 wide beam




DFL200 with DFL200LENS60

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	DIMENSIONS L x W x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
DFL30/4	Black high powered flood 4000k	30W	300 x 240 x 69	SMD LED	4050lm	> 135
DFL30/6	Black high powered flood 6000k	30W	300 x 240 x 69	SMD LED	4050lm	> 135
DFL50/4	Black high powered flood 4000k	50W	300 x 240 x 69	SMD LED	6250lm	> 125
DFL50/6	Black high powered flood 6000k	50W	300 x 240 x 69	SMD LED	6250lm	> 125
DFL100/4	Black high powered flood 4000k	100W	335 x 295 x 71	SMD LED	12500lm	> 125
DFL100/6	Black high powered flood 6000k	100W	335 x 295 x 71	SMD LED	12500lm	> 125
DFL150/4	Black high powered flood 4000k	150W	375 x 320 x 75	SMD LED	18750lm	> 125
DFL150/6	Black high powered flood 6000k	150W	375 x 320 x 75	SMD LED	18750lm	> 125
DFL200/4	Black high powered flood 4000k	200W	400 x 345 x 78	SMD LED	25000lm	> 125
DFL200/6	Black high powered flood 6000k	200W	400 x 345 x 78	SMD LED	25000lm	> 125
DFL300/4	Black high powered flood 4000k	300W	464 x 410 x 83	SMD LED	37500lm	> 125
DFL300/6	Black high powered flood 6000k	300W	464 x 410 x 83	SMD LED	37500lm	> 125


ACCESSORIES

DFLADPT/42	Pole mounting adaptor for 42mm poles
DFLADPT/60	Pole mounting adaptor for 60mm poles
DFLADPT/76	Pole mounting adaptor for 76mm poles
DFLCLAMP	Pole mounting clamp


- Asymmetric Type 1, 2 and 3 lens available
- 15/30/60/90 degree lens available



Type 1



Type 2



Type 3



Clamp installation



Pole mounting adaptor