

# Specification - Com Lite Foodsafe Highbay

Revision 1



Product Information	
<b>Model No.</b>	FS150/4      FS200/4
<b>Power Consumption(±5%)</b>	150w/200w
<b>Power Supply</b>	Com Lite brand
<b>Input Voltage</b>	120-240 VAC, 50-60Hz
<b>Power Factor</b>	>0.90
<b>Driver Type</b>	Constant Current
<b>LED Type</b>	SMD
<b>Luminous Flux (±10%) 4000k Ra80</b>	21440/28865lm
<b>Optic</b>	120 degree (option of 60 or 90 degrees)
<b>Efficiency (4000k)</b>	> 140lm per watt
<b>CCT</b>	4000k
<b>Color Rendering Index</b>	Ra80
<b>Surge Protection</b>	6kV line-line, 10kV line-earth
<b>Class</b>	Class I
<b>SCDM</b>	< 6
<b>IK rating</b>	IK10
<b>IP Rating</b>	IP66
<b>Colour</b>	RAL9007 (Grey)
<b>Dimensions</b>	489mm diameter x 200mm height
Options	
<b>Dimmable</b>	Dali, 1-10v
<b>Emergency</b>	Standard, self test, Dali self test (Remote)
<b>Sensor</b>	Remote



## Applications

Food production , Warehouses

## Lifespan and Warranty

<b>Lifetime of LED @ Ta=25°C</b>	> 114,000hrs L80B30
<b>Warranty</b>	5 years