

## Specification - Com Lite CDCP Models (Clear Frosted Diffuser)



Product Information		
Model No.	CDCP27	CDCP45
Power Consumption(±5%)	25w	45w
Power Supply	Tridonic or European Brand	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD	
Luminous Flux (±10%) 4000k	3700lm	6500lm
Luminous Flux (±10%) 5000k	3720lm	6510lm
Efficiency	> 145lm per watt	> 140lm per watt
CCT	4000k or 5000k	
Color Rendering Index	Ra80	
Beam Angle	120 degrees	
Class	Class I	
SCDM	< 6	
IK rating	IK08	
IP Rating	IP65	
Clips	304 stainless steel x 12pcs	
Dimensions (mm)	1500x100x73	1500x100x73
Options		
Dimmable	Dali, DSI, 1-10v, Triac	
Emergency	Standard, self test, Dali self test	
Sensors	Inbuilt microwave , batten mount PIR	
Applications		
Farmyards, Garages, Plantrooms, Underground carparks, Workshops , Warehouses		
Lifespan and Warranty		
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20	
Warranty	5 years	