

COM LITE IP65 RANGE



Com Lite
Commercial Lighting

INDUSTRIAL

Com Lite IP65 Range

A Range of LED Anti-Corrosive fixtures designed with quality materials and components. Both durable and functional, the polycarbonate IP65 luminaire is the perfect solution for modernisation and renovation without the need to compromise on results. They are suitable for use in all retail, commercial and general lighting

applications where style and efficiency are both essential.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for use in retail sheds, under ground car parks and warehouses
- IK08 rated
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Through wired with connector at each end for ease of wiring (CP models)
- Zero maintenance

MATERIALS

- High quality LED chips and reliable driver
- Polycarbonate housing and polycarbonate covers
- Supplied with stainless steel clips (304)

ACCESSORIES AVAILABLE

- Can be fitted with batten mounted PIR or inbuilt microwave sensor. Add /SN or /MS after product code.
- Dimmable versions available. (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k, 5000k or 3CCT versions available
- CP65 models supplied with CREE LED and European brand driver

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

3 years and 5 year option


IP RATING

IP65


PRODUCT CODE	DESCRIPTION	WATTAGE (W)	DIMENSIONS L x W x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
CP220/5	2ft IP65 colour 5000k	20W	600 x 100 x 73	SMD LED	1900lm	> 95
CP220MC	2ft IP65 3CCT colour 3000/4000/6000k	20W	600 x 100 x 73	SMD LED	1810-1900lm	> 90
CP20/5	4ft IP65 colour 5000k	21W	1200 x 100 x 73	SMD LED	2110lm	> 100
CP20MC	4ft IP65 3CCT colour 3000/4000/6000k	21W	1200 x 100 x 73	SMD LED	1950-2110lm	> 90
CP40/5	4ft IP65 colour 5000k	41W	1200 x 100 x 73	SMD LED	3990lm	> 95
CP40MC	4ft IP65 3CCT colour 3000/4000/6000k	41W	1200 x 100 x 73	SMD LED	3700-3990lm	> 90
CP30/4	5ft IP65 colour 4000k	29W	1500 x 100 x 73	SMD LED	2800lm	> 95
CP30/5	5ft IP65 colour 5000k	29W	1500 x 100 x 73	SMD LED	2900lm	> 100
CP55/4	5ft IP65 colour 4000k	57W	1500 x 100 x 73	SMD LED	5300lm	> 90
CP55/5	5ft IP65 colour 5000k	57W	1500 x 100 x 73	SMD LED	5300lm	> 90
CP55MC	5ft IP65 colour 3000/4000/6000k	57W	1500 x 100 x 73	SMD LED	5150-5300lm	> 90
CP65/4	5ft High Output IP65 colour 4000k	67W	1500 x 100 x 73	SMD LED	8500lm	> 125
CP65/5	5ft High Output IP65 colour 5000k	67W	1500 x 100 x 73	SMD LED	8980lm	> 130

CLEAR DIFFUSER VERSIONS

CDCP27/4	5ft IP65 with clear diffuser 4000k	27W	1500 x 100 x 73	SMD LED	3710lm	> 145
CDCP45/4	5ft IP65 with clear diffuser 4000k	45W	1500 x 100 x 73	SMD LED	6500lm	> 140
CDCP45PW/4	5ft IP65 with clear diffuser 4000k prewired with 3mtrs flex	45W	1500 x 100 x 73	SMD LED	6500lm	> 140



CP65/5



CDCP45