


Specification - Com Lite Linear Highbay V1




| Product Information | | |
|---------------------------|---|----------------|
| Model No. | L150/4/MW | L200/4/MW |
| Power Consumption(±5%) | 150/113/75w | 200/150/100w |
| Power Supply | Sosen or Inventronics | |
| Input Voltage | 220-240 VAC, 50-60Hz | |
| Power Factor | >0.90 | |
| Driver Type | Constant Current | |
| LED Type | SMD led | |
| Surge Protection | 6Kv line-line, 6Kv line-Earth | |
| Luminous Flux (±10%) Ra80 | 22800/17175/11400lm 30625/23000/15300lm | |
| Efficiency | > 150lm per watt | |
| CCT | 4000k, others on special request | |
| Color Rendering Index | Ra80 | |
| Beam Angle | 120 degrees , or narrow beam (120x40 degree) available | |
| Class | Class I | |
| SCDM | < 6 | |
| IK rating | IK08 | |
| IP Rating | IP65 | |
| Colour | Black (RAL9017) | |
| Dimensions (LxWxH) | 802x102x100mm | 1024x102x100mm |
| Options | | |
| Dimmable | Dali, DSI, 1-10v | |
| Emergency | Standard, self test, Dali self test | |
| Sensor | Inbuilt Plug in PIR or Microwave sensor | |
| Accessories | | |



Rotatable bracket kit

Code: LCRBKT



Ceiling mount bracket

Triangle shape

Code: LCBKT



Plug in PIR

Code: MU/PIR (12mtrs)



Applications

Exhibition Halls, Retail, Showrooms, Sports Halls, Warehouses

Lifespan and Warranty

| | |
|----------------------------------|--------------------|
| Lifetime of LED @ Ta=25°C | > 80,000hrs L80B20 |
|----------------------------------|--------------------|

| | |
|-----------------|---------|
| Warranty | 5 years |
|-----------------|---------|