

COM LITE PANELS BACK LIT



Com Lite
Commercial Lighting

A range of back lit efficient LED panels that can be recessed into suspended ceilings.



KEY FEATURES

- 40,000 hr LED life expectancy
- Beam Angle 120 degrees
- CRI > 80
- Ideal for use in corridors, hospitals, meeting rooms, reception areas, retail environments, schools
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Suitable for standard 15mm or 24mm ceiling grids
- Zero maintenance

MATERIALS

- Iron metal powder coated body
- Opal pmma diffuser as standard
- Supplied with remote driver for ease of wiring

ACCESSORIES AND OPTIONS AVAILABLE

- Can be supplied with inbuilt microwave sensor or corridor function if used in plasterboard or suspended ceilings
- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.
- Plasterboard clips available for recessing into plasterboard ceilings. (Model LEDP/PBC for pack of 4, extra needed for sizes bigger than 595 x 595)
- Plasterboard recessed frames available for recessing into plasterboard ceilings

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

3 years

IP RATING

IP44

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
BP36/4	Recessed led panel 4000k	36W	595 x 595 x 30mm	LED	Opal Pmma	3400	> 90
BP36MC	Recessed led panel 3000/4000/5700k	36W	595 x 595 x 30mm	LED	Opal Pmma	3240/3350/3550	> 90
BP362/4	Recessed led panel 4000k	36W	1195 x 295 x 30mm	LED	Opal Pmma	3400	> 90
BP362MC	Recessed led panel 3000/4000/5700k	36W	1195 x 295 x 30mm	LED	Opal Pmma	3240/3350/3550	> 90
BP60/4	Recessed led panel 4000k	60W	1195 x 595 x 30mm	LED	Opal Pmma	5400	> 90
BP60MC	Recessed led panel 3000/4000/5700k	60W	1195 x 595 x 30mm	LED	Opal Pmma	5400/5500/5600	> 90