COM LITE POST TOP













High performance, ultra efficient post top ideal for any residential areas or roadways. Built with longevity in mind these streetlights are truly maintainance free.



KEY FEATURES

- > 50,000hrs life expectancy
- CRI > 80
- IK08 rated
- Ideal for use in carparks, housing estates, parks, roadways, yards and walkways
- IP66 rated
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Preflexed for ease of installation
- Zero maintenance

MATERIALS

- Diecast aluminium body and polycarbonate diffuser
- High output led chip used
- Reliable inbuilt driver

ADDITIONAL INFORMATION

- 3500k supplied as standard, 4000k-6000k available on special order
- Suitable for 60mm poles but adaptors available for other sizes
- Working temperature -30 to +50 degrees

DIMMABLE OPTIONS

- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable


WARRANTY

5 years

IP RATING

IP66









Typical installation

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	DIMENSIONS Dia x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
PT60/35	Charcoal 60W post top 3500k	60W	420 x 390	SMD LED	7200lm	> 115
PT100/35	Black 100W post top 3500k	100W	450 x 526	SMD LED	12000lm	> 115

ACCESSORIES DESCRIPTION

ADPT76	76mm pole adaptor
PC	Photocell control option





