

Specification - Com Lite Suspended Halo

Revision 1



Product Information

| | |
|--|-------------------------|
| Model No. | SUS25W |
| Power Consumption(±5%) | 25w |
| Power Supply | Triac dimmable Com Lite |
| Input Voltage | 220-240 VAC, 50-60Hz |
| Power Factor | >0.90 |
| Driver Type | Constant Current |
| LED Type | SMD led |
| Luminous Flux (±10%) 3000k Ra80 | 1850lm |
| Luminous Flux (±10%) 4000k Ra80 | 2025lm |
| Efficiency (4000k) | > 80lm per watt |
| CCT | 3000k or 4000k |
| Color Rendering Index | Ra80 |
| Beam Angle | 120 degrees |
| Class | Class II |
| SCDM | < 6 |
| IK rating | IK06 |
| IP Rating | IP40 |
| Colour | Silver |
| Dimensions (Dia x H) | 298x50 |
| Options | |
| Dimmable | Triac as standard |
| Emergency | No option |
| Sensor | Remote sensor only |

Applications

Board Rooms, Corridors, Hotels, Reception Area's, Retail

Lifespan and Warranty

| | |
|----------------------------------|--------------------|
| Lifetime of LED @ Ta=25°C | > 50,000hrs L80B20 |
| Warranty | 3 years |