

Specification - Com Lite Low UGR TPA Panels

Revision 1



Product Information					
Model No.	TPA23LG/4	TPA30LG/4	TPA40LG/4	TPA302LG/4	TPA60LG/4
Power Consumption(±5%)	23w	30w	38w	30w	60w
Power Supply	Eaglerise, Lifud or premium brand				
Input Voltage	220-240 VAC, 50-60Hz				
Power Factor	>0.90				
Driver Type	Constant Current				
LED Type	SMD led				
UGR	<19				
Luminous Flux (±10%) 4000k Ra80	2850lm	3650lm	4610lm	3650lm	7200lm
Efficiency (4000k)	> 120lm per watt				
CCT	4000k				
Color Rendering Index	Ra80				
Beam Angle	90 degrees				
Class	Class II				
SCDM	< 6				
IK rating	IK06				
IP Rating	IP44				
Colour	White				
Diffuser Material	TP(a)				
Dimensions	595x595x28mm	595x595x28mm	595x595x28mm	1195x295x28mm	1195x595x28mm
Options					
Dimmable	Dali, DSI, 1-10v, Triac				
Emergency	Standard, self test, Dali self test				
Sensor	Remote sensor only				
Applications					
Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail					
Accessories					
Surface Mount Frame	PSF600/600BL	PSF600/600BL	PSF600/600BL	PSF1200/300BL	PSF1200/600BL
Recessed Mount Frame	PRF600/600	PRF600/600	PRF600/600	PRF1200/300	PRF1200/600
Suspension Kits	SUSKIT/3M (4 wire 3mtr suspension kit)				
	SUSKIT/5M (4 wire 5mtr suspension kit)				
	SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)				
Plasterboard Clips	LEDP/PBC (set of 4)				
Lifespan and Warranty					
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20				
Warranty	5 years				