

# Specification - Com Lite Low UGR TPA Panels

Revision 1



Product Information					
<b>Model No.</b>	TPA23LG/4	TPA30LG/4	TPA40LG/4	TPA302LG/4	TPA60LG/4
<b>Power Consumption(±5%)</b>	23w	30w	38w	30w	60w
<b>Power Supply</b>	Eaglerise, Lifud or premium brand				
<b>Input Voltage</b>	220-240 VAC, 50-60Hz				
<b>Power Factor</b>	>0.90				
<b>Driver Type</b>	Constant Current				
<b>LED Type</b>	SMD led				
<b>UGR</b>	<19				
<b>Luminous Flux (±10%) 4000k Ra80</b>	2850lm	3650lm	4610lm	3650lm	7200lm
<b>Efficiency (4000k)</b>	> 120lm per watt				
<b>CCT</b>	4000k				
<b>Color Rendering Index</b>	Ra80				
<b>Beam Angle</b>	90 degrees				
<b>Class</b>	Class II				
<b>SCDM</b>	< 6				
<b>IK rating</b>	IK06				
<b>IP Rating</b>	IP44				
<b>Colour</b>	White				
<b>Diffuser Material</b>	TP(a)				
<b>Dimensions</b>	595x595x28mm	595x595x28mm	595x595x28mm	1195x295x28mm	1195x595x28mm
Options					
<b>Dimmable</b>	Dali, DSI, 1-10v, Triac				
<b>Emergency</b>	Standard, self test, Dali self test				
<b>Sensor</b>	Remote sensor only				
Applications					
Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail					
Accessories					
<b>Surface Mount Frame</b>	PSF600/600BL	PSF600/600BL	PSF600/600BL	PSF1200/300BL	PSF1200/600BL
<b>Recessed Mount Frame</b>	PRF600/600	PRF600/600	PRF600/600	PRF1200/300	PRF1200/600
<b>Suspension Kits</b>	SUSKIT/3M (4 wire 3mtr suspension kit)				
	SUSKIT/5M (4 wire 5mtr suspension kit)				
	SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)				
<b>Plasterboard Clips</b>	LEDP/PBC (set of 4)				
Lifespan and Warranty					
<b>Lifetime of LED @ Ta=25°C</b>	> 50,000hrs L80B20				
<b>Warranty</b>	5 years				