

## Specification - Earth One Opal Panels

Revision 1



### Product Information

<b>Model No.</b>	LEDP483/84	LEDP60/84
<b>Power Consumption(±5%)</b>	44w	60w
<b>Power Supply</b>	European brand	
<b>Input Voltage</b>	220-240 VAC, 50-60Hz	
<b>Power Factor</b>	>0.90	
<b>Driver Type</b>	Constant Current	
<b>LED Type</b>	SMD led	

<b>Luminous Flux (±10%) 4000k Ra80</b>	4815lm	6280lm
<b>Efficiency (4000k)</b>	> 105lm per watt	
<b>CCT</b>	4000k	
<b>Colour Rendering Index</b>	Ra80	
<b>Beam Angle</b>	120 degrees	
<b>Class</b>	Class II	
<b>SCDM</b>	< 6	
<b>IK rating</b>	IK06	
<b>IP Rating</b>	IP40	
<b>Colour</b>	White	
<b>Dimensions</b>	1195x145x11mm	1495x295x11mm

### Options

<b>Dimmable</b>	Dali, DSI, 1-10v, Triac
<b>Emergency</b>	Standard, self test, Dali self test
<b>Sensor</b>	Remote sensor only

### Applications

Board Rooms, Corridors, Hotels, Offices, Reception Area's, Hospitals, Retail



**Tegral**  
Quality Lighting

### Accessories

**Surface Mount Frame** PSF1200/150 PSF1500/300

**Suspension Kits** SUSKIT/3M (4 wire 3mtr suspension kit) 2 kits needed for 1500x300  
SUSKIT/5M (4 wire 5mtr suspension kit) 2 kits needed for 1500x300

**Plasterboard Clips** LEDP/PBC (set of 4) 2 sets needed for 1500x300

### Lifespan and Warranty

**Lifetime of LED @ Ta=25°C** > 50,000hrs L80B20

**Warranty** 5 years