

Specification - Earth One Opal Panels

Revision 1



Product Information

Model No.	LEDP483/84	LEDP60/84
Power Consumption(±5%)	44w	60w
Power Supply	European brand	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD led	

Luminous Flux (±10%) 4000k Ra80	4815lm	6280lm
Efficiency (4000k)	> 105lm per watt	
CCT	4000k	
Colour Rendering Index	Ra80	
Beam Angle	120 degrees	
Class	Class II	
SCDM	< 6	
IK rating	IK06	
IP Rating	IP40	
Colour	White	
Dimensions	1195x145x11mm	1495x295x11mm

Options

Dimmable	Dali, DSI, 1-10v, Triac
Emergency	Standard, self test, Dali self test
Sensor	Remote sensor only

Applications

Board Rooms, Corridors, Hotels, Offices, Reception Area's, Hospitals, Retail



Tegral
Quality Lighting

Accessories

Surface Mount Frame PSF1200/150 PSF1500/300

Suspension Kits SUSKIT/3M (4 wire 3mtr suspension kit) 2 kits needed for 1500x300
SUSKIT/5M (4 wire 5mtr suspension kit) 2 kits needed for 1500x300

Plasterboard Clips LEDP/PBC (set of 4) 2 sets needed for 1500x300

Lifespan and Warranty

Lifetime of LED @ Ta=25°C > 50,000hrs L80B20

Warranty 5 years