

## Specification - Earth Suspended Polo Series

Revision 1



Product Information			
Model No.	SP600P	SP900P	SP1200P
Power Consumption(±5%)	56w	102w	133w
Power Supply	European brand		
Input Voltage	220-240 VAC, 50-60Hz		
Power Factor	>0.90		
Driver Type	Constant Current		
LED Type	SMD led		
Other wattages available	< 56w	150w/< 102w	<133w
Luminous Flux (±10%) 4000k Ra80	6100lm	10540lm	13995lm
Efficiency (4000k)	> 105lm per watt	> 100lm per watt	> 100lm per watt
CCT	4000k with options of 3000k and 6000k		
Color Rendering Index	Ra80		
Beam Angle	100 degrees		
Class	Class I		
SCDM	< 6 (SCDM3 on request)		
IK rating	IK06		
IP Rating	IP40		
Colour	Black, White or any colour to special order		
Dimensions (Dia x H)	600x90mm	900x90mm	1200x90mm
Options			
Dimmable	Dali, DSI, 1-10v, Triac		
Emergency	Standard, self test, Dali self test		
Sensor	Remote sensor only		
Applications			
Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail			
Lifespan and Warranty			
Lifetime of LED @ Ta=25°C	> 70,000hrs L80B20		
Warranty	5 years		