

EARTH SUSPENDED/SURFACE - SP600



A range of decorative circular high end fixtures suitable for suspension or surface mounting. Ideal for retail and commercial applications where design, energy saving and functionality are as important as reliability.



KEY FEATURES

- 50,000 hr LED life expectancy
- Available in Black and White as standard
- CRI > 80
- L80B10 @ 50,000hrs, Ta = 25 degrees
- Manufactured with Samsung Led and European brand driver
- PF > 0.90
- Zero maintenance

MATERIALS

- Diffuser made from Opal pmma
- Samsung LED and European brand driver
- Sheet Steel housing

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency

ADDITIONAL INFORMATION

- 4000k available as standard and 3000k available to special order
- 3 mtr suspension kit supplied as standard, additional lengths available upon request
- Surface bracket available, order ref SP/SBK

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

5 years

IP RATING

IP40

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	SIZE DIA x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
SP600/60/84/BK	Circular pendant lighting fixture Black	60W	600 x 90	SMD LED	Opal Pmma	6000lm	> 100
SP600/60/84/WH	Circular pendant lighting fixture White	60W	600 x 90	SMD LED	Opal Pmma	6000lm	> 100
SP600/100/84/BK	Circular pendant lighting fixture Black	100W	600 x 90	SMD LED	Opal Pmma	10000lm	> 100
SP600/100/84/WH	Circular pendant lighting fixture White	100W	600 x 90	SMD LED	Opal Pmma	10000lm	> 100