

EARTH SUSPENDED - SP900



A centrepiece decorative circular fixture suitable for suspension only. Ideal for retail and commercial applications where design, energy saving and functionality are as important as reliability.



KEY FEATURES

- 50,000 hr LED life expectancy
- Available in White as standard but other RAL colours available upon request
- CRI > 80
- L80B10 @ 50,000hrs Ta 25 degrees
- Manufactured with Samsung Led and European brand driver
- PF > 0.90
- Zero maintenance

MATERIALS

- Diffuser made from Opal pmma
- Samsung LED and European brand driver
- Sheet Steel housing

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k available as standard and 3000k available to special order
- 5 mtr suspension kit supplied as standard, additional lengths available upon request

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

5 years

IP RATING

IP40

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	SIZE DIA x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
SP900/100/84/WH	Circular pendant donut lighting fixture White	100W	900 x 80	SMD LED	Opal Pmma	10000lm	> 100
SP900/150/84/WH	Circular pendant donut lighting fixture White	150W	900 x 80	SMD LED	Opal Pmma	15000lm	> 100