



**Tegral**  
Quality Lighting

## Specification - Earth Two

Revision 1



### Product Information

Model No.	T60030/4
Power Consumption(±5%)	30w
Power Supply	Philips or European brand
Input Voltage	220-240 VAC, 50-60Hz
Power Factor	>0.90
Driver Type	Constant Current
LED Type	SMD led
UGR	<21
Luminous Flux (±10%) 4000k Ra80	3500lm
Efficiency (4000k)	> 115lm per watt
CCT	4000k
Colour Rendering Index	Ra80
Beam Angle	90 degrees
Class	Class I
SCDM	< 3
IK rating	IK06
IP Rating	IP20
Colour	White (RAL9003)
Dimensions	595x595x50mm

### Options

Dimmable	Dali, DSI, 1-10v, Triac
Emergency	Standard, self test, Dali self test
Sensor	Inbuilt PIR or Remote PIR/microwave sensor

### Applications

Board Rooms, Corridors, Hotels, Reception Area's, Offices, Retail

### Accessories

Surface Mount Frame	PSF600/600BL
Recessed Mount Frame	PRF600/600
Suspension Kits	SUSKIT/3M (4 wire 3mtr suspension kit) SUSKIT/5M (4 wire 5mtr suspension kit) SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)



**Tegral**  
Quality Lighting

**Lifespan and Warranty**

**Lifetime of LED @ Ta=25°C**

> 80,000hrs L80B20

**Warranty**

5 years