

EARTH TWO



A range of highly efficient backlit LED panels. These are ideal replacements for many forms of traditional fluorescent recessed or surface fixtures.



COMMERCIAL RECESSED ▶ Earth Two

MATERIALS

- European brand driver
- High quality heat sink
- Made with Samsung LEDs
- Three part opal pmma supplied as standard

ACCESSORIES AND OPTIONS AVAILABLE

- Can be supplied with inbuilt microwave sensor or corridor function if used in plasterboard or suspended ceilings
- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.
- Plasterboard recessed frames available for recessing into plasterboard ceilings

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

5 years

IP RATING

IP20

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	SIZE L x W x H (mm)	CUT OUT (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
T312LED	Recessed panel white frame 4000k	36W	595 x 595 x 30	580 x 580	LED	Opal Pmma	3300lm	> 90

ACCESSORIES

LEDP36RF	Recessed frame for plasterboard ceiling for 595 x 595mm panels
----------	--