

# JUPITER TWO DIRECT/INDIRECT LOW GLARE



A range of suspended linear low glare fittings made with quality materials with direct/indirect backlit light diffusion. The Jupiter Two low glare option is an ideal solution for energy saving in an office environment whilst not needing to compromise on the efficiency and integrity of the space. They offer an elegant and modern design aesthetic suitable for

use in all commercial lighting installations with an emphasis on boardrooms, call centres, open plan office and reception areas.



## KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Light output 80% down and 20% upwards
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Preflexed for ease of installation
- Zero maintenance

## MATERIALS

- Complete with suspension kit as standard (2mtrs)
- European branded control gear
- High quality sheet steel body painted to RAL9003
- Pmma diffuser

## ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

## ADDITIONAL INFORMATION

- 4000k-4200k supplied as standard. 3000k also available to special order
- Choice of RAL colours available

## DIMMABLE OPTIONS


- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

## WARRANTY

5 years

## IP RATING

IP20



TSDIDL60WH

PRODUCT CODE	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
TSDIDL650WH	50W	1300 x 200 x 31	LED	Microprismatic	4630lm	> 90
TSDIDL660WH	60W	1600 x 200 x 31	LED	Microprismatic	6000lm	> 100