

JUPITER TWO DIRECT/INDIRECT



A range of suspended linear fittings made with quality materials, components and LED boards with direct/indirect backlit light diffusion. The Jupiter Two range is the solution to your requirement for energy saving lighting whilst not needing to compromise on the efficiency and integrity of the space. They offer an elegant and modern design

aesthetic suitable for use in all retail and commercial lighting installations with an emphasis on boardrooms, open plan areas, retail space, reception areas and halls.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Light output 70% down and 30% upwards
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Preflexed for ease of installation
- Zero maintenance

MATERIALS

- Complete with suspension kit as standard (2mtrs)
- European branded control gear
- High quality aluminium alloy body with white finish
- Manufactured with Samsung LED chips
- Opal polycarbonate diffuser

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k-4200k supplied as standard, if 3000k-3200k or 6000-6500k is needed please add /83 or /86 at end of product code.

DIMMABLE OPTIONS


- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable

WARRANTY

5 years

IP RATING

IP20



TSDID75

PRODUCT CODE	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
TSDID75	71W	1515 x 245 x 65	LED	Opal	6530lm	> 90