

# MERCURY ONE



A traditional style low glare louvre with high efficiency made with European brand LED boards and driver.



## KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for use in office and school environments
- L80B10 @ 50,000hrs, Ta = 25 degrees
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Suitable for standard 15mm or 24mm ceiling grids
- Zero maintenance

## MATERIALS

- European brand chips and driver
- High-purity polished anodized aluminum, double parabolic louvre
- Sheet Steel housing
- Diffuser made from Mat Opal pmma

## ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available (see dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency
- Clips available for plasterboard ceilings. (Order ref C/CLIPS for packet of 4)

## ADDITIONAL INFORMATION

- 3000k or 4000k available

## DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

## WARRANTY


5 years

## IP RATING

IP20

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN	LUMEN PER CIRCUIT WATT
TL32W/83	Recessed 600x600 louvred fitting 3000k	32W	595 x 595 x 53	SMD LED	Pmma	3470lm	> 105
TL32W/84	Recessed 600x600 louvred fitting 4000k	32W	595 x 595 x 53	SMD LED	Pmma	3670lm	> 110

Other sizes available on special order (1200x300, 1200x600, 1500x300)



TL32W