

# MOON ONE



A range of recessed indirect modular fittings made with quality components and LED boards. The indirect lighting of the Moon One LED allows for anti-glare diffused illumination without a compromise on style. The Moon range is the answer to the need for high end aesthetics in a workspace

environment. They are the perfect solution for modernisation to energy saving where the aesthetics are vital without the need to compromise on results. They are suitable for all commercial environments, with a special emphasis on call centres, open plan

offices, reception areas and back offices.



## KEY FEATURES

- 50,000 hr life expectancy
- CRI > 80
- Ideal for use in office environments
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Suitable for standard 15mm or 24mm ceiling grids
- UGR < 19
- Zero maintenance

## MATERIALS

- European branded driver
- High quality steel body
- Indirect cover for soft illumination

## ACCESSORIES AND OPTIONS AVAILABLE

- Available with inbuilt PIR sensor
- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.
- Mounting clips available for plasterboard ceilings, use model no C/CLIPS

## ADDITIONAL INFORMATION

- 4000k-4200k supplied as standard, if 3000k-3200k or 6000k-6500k is needed please add /83 or /86 at end of product code

## DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

## WARRANTY

5 years

## IP RATING

IP20



Typical installation

PRODUCT CODE	WATTAGE (W)	SIZE L x W x H (mm)	CUT OUT (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
TID220	40W	595 x 595 x 110	580 x 580	LED	Indirect	2600lm	> 65