

NEPTUNE 65



A range of IP65 recessed downlights with opal polycarbonate lens designed with quality materials, components & SMD LED lightsource. These high efficiency energy saving luminaires are available in a range of sizes, wattages and colour renderings. They are suitable for all retail and commercial

lighting installations with an emphasis on the exterior canopy areas, clean rooms, restrooms, laboratories, and wet rooms.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for use in bathrooms, carehomes, canopies, hotels, restrooms and retail
- Manufactured with quality materials and reliable European brand driver
- PF > 0.90
- Zero maintenance

MATERIALS

- Complete with SMD LED light source
- Die cast aluminium construction
- European branded LED driver

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k supplied as standard, any other colour rendering is special order

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

5 years

IP RATING

IP65



Typical installation

PRODUCT CODE	WATTAGE (W)	DIMENSIONS Dia x Depth (mm)	CUT OUT (mm)	LIGHT SOURCE	DIFFUSER TYPE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
TDL15WLED/84/65	15W	190 x 47	165 -175	SMD LED	Opal PC	1500lm	> 100
TDL25WLED/84/65	25W	235 x 55	205 - 215	SMD LED	Opal PC	2550lm	> 100
TDL25WLED/MC/65	25W	235 x 55	205 - 215	SMD LED	Opal PC	2400/2500/2490	95-100
TDL35WLED/MC/65	35W	235 x 55	205 - 215	SMD LED	Opal PC	3040/3570/3490	85-100