

Specification - Neptune Surface Cans

Revision 1



Product Information

Model No.	SC20BK/GR/WH	SC30BK/GR/WH
Power Consumption(±5%)	20w	29w
Power Supply	Philips or European Brand	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	COB	
Luminous Flux (±10%) 3000k Ra80	1900lm	2540lm
Luminous Flux (±10%) 4000k Ra80	2100lm	2800lm
Efficiency (4000k)	>95lm per watt	
CCT	3000k or 4000k	
Color Rendering Index	Ra80	
Beam Angle	40 degrees	
Class	Class I	
SCDM	< 6	
IP Rating	IP20	
Colour	Black, Grey or White	
Dimensions (Dia x H)	154x130mm	182x170mm

Options

Dimmable	Dali, 1-10v, Triac
Emergency	Standard, self test, Dali self test (all only in 30w size body)
Sensor	Remote only

Applications

Apartment complexes, Board Rooms, Corridors, Hotels, Reception Area's, Retail



Accessories



Model: SCWH/SUSKIT



Model: SCBK/SUSKIT

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 59,000hrs L80B10
Warranty	5 years