

NEPTUNE TWO



A range of recessed downlights designed with quality materials components & COB LED lightsource. These high efficiency energy saving luminaires are supplied with a frosted dropglass diffusion for a decorative look, making them the perfect solution for modernisation and energy saving without the need

to compromise on results. They are suitable for all retail and commercial lighting installations with an emphasis on corridors, retail and reception spaces.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for use in boardrooms, carehomes, residential, retail and showrooms
- Manufactured with quality materials and reliable European brand driver
- PF > 0.90
- Zero maintenance

MATERIALS

- Complete with COB LED lightsource
- European branded LED driver
- Heavy duty diecast heat sink and sheet metal body
- Supplied with frosted glass diffuser

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k supplied as standard

DIMMABLE OPTIONS


- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

5 year warranty

IP RATING

IP20



DL20DG



Typical Installation

PRODUCT CODE	WATTAGE (W)	SIZE Dia x Depth (mm)	CUT OUT (mm)	LIGHT SOURCE	DIFFUSER TYPE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
DL20DG/84	20W	190 x 185	175	COB LED	Frosted drop glass	2100lm	> 85
DL30DG/84	30W	235 x 220	220	COB LED	Frosted drop glass	2790lm	> 80