ORBIT ONE















A range of highly efficient ceiling or wall mounted traditional style bulkheads. Suitable for use in apartment blocks, bathrooms, bedrooms, carehomes, corridors, hotels, stairwells and all commercial or domestic applications.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- IP54 Rated
- · Manufactured with quality materials and reliable driver
- PF > 0.90
- Zero maintenance

MATERIALS

- European branded driver
- ABS base & polycarbonate diffuser
- Silicon gasket seal, moisture & dustproof up to IP54

ACCESSORIES AVAILABLE

- Can be fitted with inbuilt microwave sensor, please add /MS on end of product code
- Can be fitted with inbuilt corridor function, please add /CF on end of product code
- Chrome ring available please order separately under ref CR/RING
- Dimmable versions available. (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency
- Night Light available. Please add NL to end of product code.

ADDITIONAL INFORMATION

- Comes with BESA box knockouts on base
- Complete with hinged geartray for easy installation

DIMMABLE OPTIONS


- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for leading/trailing edge dimmable

WARRANTY

5 years

IP RATING

IP54







Typical installation

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	SIZE Dia x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
C14WLED/84	Circular white bulkhead 4000k	13W	320 x 90	SMD LED	990lm	> 75
C14WLED/MC	Circular white bulkhead 3CCT 3000/4000/6000K	13W	320 x 90	SMD LED	990lm	> 75
C20WLED/84	Circular white bulkhead 4000k	18W	320 x 90	SMD LED	1400lm	> 75
C20WLED/MC	Circular white bulkhead 3CCT 3000/4000/6000K	18W	320 x 90	SMD LED	1400lm	> 75



