

PLUTO 54 V2



A range of IP54 surface mounted linear fittings designed with quality materials, components and LED boards. These high efficiency luminaires are available in a range of outputs and sizes making them the perfect solution for energy saving lighting whilst not compromising on the efficiency and integrity of the space. They are suitable for all

retail and commercial lighting installations with an emphasis on carehomes, classrooms, corridors, hospitals or office space.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for general lighting in colleges, corridors, hospitals, leisure and schools
- Made with heavy duty polycarbonate diffuser and endcaps
- Manufactured with quality materials and reliable European brand driver
- PF > 0.90
- Screwed endcaps for extra security
- Zero maintenance

MATERIALS

- European branded control gear
- High quality steel body with screw type end caps
- Supplied with Opal polycarbonate diffuser

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Please add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k-4200k supplied as standard, if 3000k-3200k or 6000-6500k is needed please add /83 or /86 at end of product code.
- Benefit of conduit entry via endcaps

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable

WARRANTY

5 years

IP RATING

IP54

PRODUCT CODE	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
TS36LEDOP/IP54V2	36W	1212 x 173 x 54	SMD LED	Opal PC	4900lm	> 125
TS45LEDOP/IP54V2	45W	1512 x 173 x 54	SMD LED	Opal PC	6300lm	> 125
TS67LEDOP/IP54V2	67W	1515 x 173 x 54	SMD LED	Opal PC	8600lm	> 125