

PLUTO ONE



A range of surface mounted linear fittings designed with quality materials & components and supplied with or wired for T8 LED lamps. These high efficiency luminaires are available in a range of sizes and polycarbonate diffusion options, making them the perfect solution for energy saving lighting whilst not needing to

compromise on the efficiency and integrity of the space. They are suitable for all retail and commercial lighting installations with an emphasis on carehomes, classrooms, corridors, hospitals or office space.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for pelmet lighting or for retrofitting existing luminaires
- Manufactured with quality materials and reliable European brand driver
- PF > 0.90
- Screwed endcaps for extra security
- Zero maintenance

MATERIALS

- Available with opal or prismatic polycarbonate diffuser
- High quality steel body with screw type end caps

ACCESSORIES AND OPTIONS AVAILABLE

- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.
- Wired for LED lamp options can be wired to customer specification on request

ADDITIONAL INFORMATION

- 4000k-4200k supplied as standard, if 3000k-3200k or 6000k-6500k is needed please add /83 or /86 at end of product code
- Lamps supplied are > RA80 and PF 0.90

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

WARRANTY

2 year lamp warranty

IP RATING

IP44

PRODUCT CODE	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	PRIMARY LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
TS118PPR	1 x 18W	1255 x 208 x 70	T8 LED lamp	Prismatic	1800lm	> 70
TS218PPR	2 x 18W	1255 x 208 x 70	T8 LED lamp	Prismatic	3600lm	> 70
TS125PPR	1 x 24W	1560 x 208 x 70	T8 LED lamp	Prismatic	2300lm	> 70
TS225PPR	2 x 24W	1560 x 208 x 70	T8 LED lamp	Prismatic	4600lm	> 70
TS118POP	1 x 18W	1255 x 208 x 70	T8 LED lamp	Opal	1800lm	> 60
TS218POP	2 x 18W	1255 x 208 x 70	T8 LED lamp	Opal	3600lm	> 60
TS125POP	1 x 24W	1560 x 208 x 70	T8 LED lamp	Opal	2300lm	> 60
TS225POP	2 x 24W	1560 x 208 x 70	T8 LED lamp	Opal	4600lm	> 60
TS118PPR/B	-	1255 x 208 x 70	Wired for single ended LED lamps	Prismatic	-	-
TS218PPR/B	-	1255 x 208 x 70	Wired for single ended LED lamps	Prismatic	-	-
TS125PPR/B	-	1560 x 208 x 70	Wired for single ended LED lamps	Prismatic	-	-
TS225PPR/B	-	1560 x 208 x 70	Wired for single ended LED lamps	Prismatic	-	-
TS118POP/B	-	1255 x 208 x 70	Wired for single ended LED lamps	Opal	-	-
TS218POP/B	-	1255 x 208 x 70	Wired for single ended LED lamps	Opal	-	-
TS125POP/B	-	1560 x 208 x 70	Wired for single ended LED lamps	Opal	-	-
TS225POP/B	-	1560 x 208 x 70	Wired for single ended LED lamps	Opal	-	-