

PLUTO THREE



A range of surface mounted linear fittings made with quality materials and components designed to accommodate T8 LED lamps or LED boards, the Pluto Three range is the solution to your requirement for effective energy saving lighting whilst not needing to compromise on the classic Cat2 design.

They are suitable for use in all retail and commercial lighting installations with an emphasis on call centres, open plan offices, reception areas and back offices.



KEY FEATURES

- 50,000hr life expectancy on led board versions.
- CRI > 80
- Ideal for office applications where a traditional look is required
- Manufactured with quality materials and reliable driver
- PF > 0.90
- UGR < 19
- Zero maintenance

MATERIALS

- High quality steel body
- European branded driver on non lamp versions
- Louvre retention via spring clip

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for trailing edge dimmable

ACCESSORIES AND OPTIONS AVAILABLE

- Dimmable versions available. (See dimmable options.)
- Dimmable versions available for non lamp versions, please see dimmable options
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.
- Wired for LED lamp options can be wired to customer specification on request

ADDITIONAL INFORMATION

- Lamps supplied are > RA80 and PF 0.90
- 4000k-4200k supplied as standard, if 3000k-3200k or 6000k-6500k is needed please add /83 or /86 at end of product code

WARRANTY

2 years on lamps and 5 years on led board versions

IP RATING

IP20



Typical installation

PRODUCT CODE	WATTAGE (W)	SIZE L x W x H (mm)	LIGHT SOURCE	COVER TYPE	PRIMARY LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
TS225C2	2 x 24W	1533 x 211 x 71	T8 LED lamp	Cat2	4600lm	> 70
TS225C2/B	-	1533 x 211 x 71	Wired for single ended LED lamps	Cat2	-	-
TS30C2	30W	1533 x 211 x 71	LED	Cat2	2550lm	> 80
TS60C2	60W	1533 x 211 x 71	LED	Cat2	5100lm	> 80