

## Specification - Saturn wallpack

Revision 1



Product Information		
Model No.	AMBHLED/MC	AMBHLED50/MC
Power Consumption(±5%)	26w	47w
Power Supply	Philips	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD led	
Luminous Flux (±10%) 4000k Ra80	3340lm	6010lm
Beam Angle	120 degrees	
Material		
Material	Aluminium Alloy and Polycarbonate lens	
Efficiency (4000k)	> 125lm per watt	
CCT	Selectable 3000/4000/6000k	
Colour Rendering Index	Ra80	
Operating Temperature	-20 to 40 degrees	
Class	Class I	
SCDM	< 6	
IK rating	IK08	
IP Rating	IP65	
Colour	Black	
Dimensions	309x275x117mm	
Options		
Dimmable	Dali, DSI, 1-10v	
Emergency	Standard, self test, Dali self test	
Sensor	Inbuilt microwave and/or photocell	
Applications		
Exterior of Carehomes, Hospitals, Public Buildings and schools		
Lifespan and Warranty		
Lifetime of LED @ Ta=25°C	> 79,000hrs L80B20	
Warranty	5 years	