

STARLITE 65 V2



INDUSTRIAL ▶ Starlite 65 V2

A range of high output, high efficiency linear style LED highbays. They are suitable for factories, retail sheds, supermarkets, or showrooms.



KEY FEATURES

- 50,000hrs L80B10 at 25 degrees
- CRI > 80
- IP65 rated
- IK10 rated
- Ideal for use in retail and warehouses
- Manufactured with quality materials and reliable driver
- Preflexed and supplied with 2mtrs of hanging chain
- PF > 0.90
- Zero maintenance

MATERIALS

- Aluminium extruded housing and fin design for better heat dissipation
- European branded control gear
- Polycarbonate opal diffuser for excellent uniformity
- Manufactured with CREE chip for excellent performance

ACCESSORIES AND OPTIONS AVAILABLE

- Can be fitted with PIR or microwave sensor. Please add /SN or /MS to end of product code
- Dimmable versions available. (See dimmable options.)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

- 4000k or 5000k supplied as standard, other colour rendering available on request

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable

WARRANTY

5 years


IP RATING

IP65



Typical installation

PRODUCT CODE	DESCRIPTION	WATTAGE (W)	DIMENSIONS L x W x H (mm)	LIGHT SOURCE	DIFFUSER TYPE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
LHB200/84	Linear extruded aluminium highbay 4000k	198W	1480 x 150 x 110	SMD LED	Opal PC	24100lm	> 120
LHB200/85	Linear extruded aluminium highbay 5000k	198W	1480 x 150 x 110	SMD LED	Opal PC	24315lm	> 120



LHB200