

Specification - Sunex One Circular

Revision 1



Product Information			
Model No.	SWW9LED	SWW30LED	SWW40LED
Power Consumption(±5%)	9w	28w	40w
Power Supply	Philips or European Brand		
Input Voltage	220-240 VAC, 50-60Hz		
Power Factor	>0.90		
Driver Type	Constant Current		
LED Type	COB		
Beam Angle	60 degrees		
Luminous Flux (±10%) 3000k Ra80	920lm	2790lm	4140lm
Luminous Flux (±10%) 4000k Ra80	950lm	2970lm	4200lm
Efficiency (4000k)	>100lm per watt	>105lm per watt	>105lm per watt
CCT	3000k , 4000k , 5000k (6000k special order)		
Colour Rendering Index	Ra80		
Class	Class I		
SCDM	< 3		
Diffuser Type	Clear Glass		
IP Rating	IP20		
Colour	White		
Dimensions (Dia x Depth)	110x60mm	190x140mm	190x140mm
Cut Out	100mm	175mm	175mm
Options			
Dimmable	Dali, 1-10v or Triac		
Emergency	Standard, self test, Dali self test		
Sensor	Remote		
Applications			

Board Rooms, Corridors, Hotels, Reception Area's, Retail

Lifespan and Warranty

Lifetime of LED @ Ta=25°C

> 50,000hrs L80B20

Warranty

5 years