

Specification - Sunex Three

Revision 1



Product Information					
Model No.	RDL115	RDL125	RDL215	RDL225	RDL315
Power Consumption(±5%)	16w	25w	32w	50w	45w
Power Supply	Philips or European Brand				
Input Voltage	220-240 VAC, 50-60Hz				
Power Factor	>0.90				
Driver Type	Constant Current				
LED Type	COB				
Beam Angle	40 degrees				
Luminous Flux (±10%) 3000k Ra80	1550lm	2550lm	3150lm	5000lm	4500lm
Luminous Flux (±10%) 4000k Ra80	1610lm	2650lm	3200lm	5100lm	4600lm
Efficiency (4000k)	>100lm per watt				
CCT	3000k or 4000k (5000k/6000k special order)				
Colour Rendering Index	Ra80				
Class	Class I				
SCDM	< 6				
IP Rating	IP20				
Colour	White (RAL9016)				
Dimensions (LxWxH)	160x160x176mm	190x190x176mm	280x160x176mm	374x190x176mm	395x160x176mm
Cut Out	130x130mm	160x160mm	250x130mm	344x160mm	365x130mm
Options					
Dimmable	Dali, 1-10v or Triac				
Emergency	Standard, self test, Dali self test				
Sensor	Remote				
Applications					
Board Rooms, Corridors, Hotels, Reception Area's, Retail					
Lifespan and Warranty					
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20				
Warranty	5 years				