

Specification - Sunex Two

Revision 1



Product Information				
Model No.	WW15LED	WW25LED	WW30LED	WW36LED
Power Consumption(±5%)	15w	25w	30w	36w
Power Supply	Philips or European Brand			
Input Voltage	220-240 VAC, 50-60Hz			
Power Factor	>0.90			
Driver Type	Constant Current			
LED Type	COB			
Beam Angle	45 degrees			
Luminous Flux (±10%) 3000k Ra80	1270lm	2295lm	2375lm	3100lm
Luminous Flux (±10%) 4000k Ra80	1330lm	2400lm	2500lm	3190lm
Efficiency (4000k)	>90lm per watt			
CCT	3000k, 4000k (5000k or 6000k special order)			
Colour Rendering Index	Ra80			
Class	Class I			
SCDM	< 6			
Diffuser Type	Clear Glass			
IP Rating	IP20			
Colour	White			
Dimensions (Dia x Depth)	145x125mm	175x125mm	190x155mm	235x180mm
Cut Out	130mm	160mm	175mm	220mm
Options				
Dimmable	Dali, 1-10v or Triac			
Emergency	Standard, self test, Dali self test			
Sensor	Remote			
Applications				
Board Rooms, Corridors, Hotels, Reception Area's, Retail				
Lifespan and Warranty				
Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20			
Warranty	5 years			