TEGRAL 65 STAINLESS STEEL













A range of stainless steel IP65 fittings suitable for general lighting in carparks, garages or commercial applications.



KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- Ideal for use in retail sheds, under ground carparks and warehouses
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Zero maintenance

MATERIALS

- High quality LED chip and European branded control gear
- · Stainless steel body and tempered glass cover

ACCESSORIES AVAILABLE

- · Can be fitted with inbuilt microwave sensor
- Dimmable versions available (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.

ADDITIONAL INFORMATION

 4000k supplied as standard. 3000k or 6000k available on request

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable

WARRANTY

5 years

IP RATING







Typical installation

	PRODUCT CODE	DESCRIPTION	WATTAGE (W)	DIMENSIONS L x W x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
	T5TSS50/65	5ft linear IP65 stainless steel 4000k	50W	1600 x 132 x 90mm	SMD LED	6000lm	> 115