

Specification - Saturn asymmetrical wallpack

CE Black RAL9005	Grey RAL7016	
Product Information		
Model No.	ASWP/4	
Power Consumption(±5%)	selectable 13/18/28w	
Power Supply	TCI or European Brand	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Туре	SMD led	
Luminous Flux (±10%) 4000k Ra80	1700lm/2350lm/3510lm	
Material	Diecast body and Polycarbonate diffuser	
Efficiency (4000k)	> 130lm per watt	
ССТ	4000k	
Colour Rendering Index	Ra80	
Operating Temperature	-10 to 35 degrees	
Class	Class I	
SCDM	< 6	
IK rating	IK10	
IP Rating	IP65	
Colour	Black (RAL9005) or Grey (RAL7016) 319x165x265mm	
Dimensions	3198103820311111	

Options	
Dimmable	Dali, DSI, 1-10v, Traic
Emergency	Standard, self test, Dali self test
Sensor	Inbuilt microwave or photocell

Applications

Carehomes, Hospitals, Stairwells, Public Buildings and schools

Lifespan and Warranty	
Lifetime of LED @ Ta=25°C	> 60,000hrs L80B20
Warranty	5 years

Revision 1