

Specification - Com Lite Battens

Revision 1



Product Information			
Model No.	CBAT4MW	CBAT5MW	CBAT6MW
Power Consumption(±5%)	22/30/35/40w	32/40/50/60w	36/45/55/65w
Power Supply	Boke		
Input Voltage	220-240 VAC, 50-60Hz		
Power Factor	>0.90		
Driver Type	Constant Current		
LED Type	0.5w SMD		
Luminous Flux (±10%) 4000k Ra80 (highest power)	5035lm	7585lm	9080lm
Luminous Flux (±10%) 4000k Ra80 (lowest power)	3070lm	4595lm	5350lm
Efficiency (4000k)	> 135lm per watt		
CCT	selectable 3000k/4000k/6000k		
Colour Rendering Index	Ra80		
Beam Angle	120 degrees		
Class	Class I		
SCDM	< 6		
IK rating	IK06		
IP Rating	IP20		
Colour	RAL9003		
Dimensions	1178x61x71mm	1478x61x71mm	1778x61x71mm
Options			
Dimmable	Dali, DSI, 1-10v, Triac		
Emergency	Standard, self test, Dali self test		
Sensor	Inbuilt microwave or batten mount PIR		



Applications

Garages, Hospitals, Retail, Warehouses

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 50,000hrs L80B20
Warranty	5 years