

# Specification - Com Lite CES Models

Revision 1



## Product Information

<b>Model No.</b>	CES18WH/MC	CES25WH/MC		
<b>Power Consumption(±5%)</b>	17w	25w		
<b>Power Supply</b>	Com Lite			
<b>Input Voltage</b>	220-240 VAC, 50-60Hz			
<b>Power Factor</b>	>0.90			
<b>Driver Type</b>	Constant Current			
<b>LED Type</b>	SMD led			
<b>Luminous Flux (±10%) 3000k Ra80</b>	1810lm	2730lm		
<b>Luminous Flux (±10%) 4000k Ra80</b>	1950lm	2890lm		
<b>Efficiency (4000k)</b>	> 115lm per watt			
<b>CCT</b>	3000/4000/5700k selectable			
<b>Colour Rendering Index</b>	Ra80			
<b>Beam Angle</b>	120 degrees			
<b>Class</b>	Class II			
<b>SCDM</b>	< 6			
<b>IK rating</b>	IK10			
<b>IP Rating</b>	IP54			
<b>Colour</b>	White (RAL9016)			
<b>Diffuser Material</b>	Polycarbonate			
<b>Body Material</b>	Polycarbonate			
<b>Dimensions (Diax Depth)</b>	275x65mm	275x65mm	350x65mm	350x65mm
<b>Operating Temperature</b>	-10°C ~40°C			

## Options

<b>Dimmable</b>	Dali, 1-10v
<b>Emergency</b>	Standard or self test
<b>Sensor</b>	Inbuilt microwave or Remote

## Applications

Corridors, Hotels, Reception Area's, Stairwells



## Accessories

Black or Silver finish available as options

## Lifespan and Warranty

Lifetime of LED @ Ta=25°C	>40,000hrs L70B50
Warranty	3 years (5 year option)