

Specification - Com Lite CES Models

Revision 1



Product Information				
Model No.	CES18WH/MC	CES25WH/MC		
Power Consumption(±5%)	18w	25w		
Power Supply	Com Lite			
Input Voltage	220-240 VAC, 50-60Hz			
Power Factor	>0.90			
Driver Type	Constant Current			
LED Type	SMD led			
Luminous Flux (±10%) 3000k Ra80	1810lm	2730lm		
Luminous Flux (±10%) 4000k Ra80	1950lm	2890lm		
Efficiency (4000k)	> 115lm per watt			
CCT	3000/4000/5700k selectable			
Colour Rendering Index	Ra80			
Beam Angle	120 degrees			
Class	Class II			
SCDM	< 6			
IK rating	IK10			
IP Rating	IP54			
Colour	White (RAL9016)			
Diffuser Material	Polycarbonate			
Body Material	Polycarbonate			
Dimensions (Diax Depth)	275x65mm	275x65mm	350x65mm	350x65mm
Operating Temperature	-10°C ~40°C			
Options				
Dimmable	Dali, 1-10v			
Emergency	Standard or self test			
Sensor	Inbuilt microwave or Remote			

Applications

Corridors, Hotels, Reception Area's, Stairwells



Accessories

Black or Silver finish available as options

Lifespan and Warranty

Lifetime of LED @ Ta=25°C

>40,000hrs L70B50

Warranty

3 years (5 year option)