

Specification - Com Lite High Efficiency Low UGR 3CCT

Revision 1



Product Information					
Model No.	CHL20LG/MC	CHL30LG/MC	CHL202LG/MC	CHL302LG/MC	CHL403LG/MC
Power Consumption(±5%)	19w	30w	20w	30w	40w
Power Supply	Lifud or European brand on request				
Input Voltage	220-240 VAC, 50-60Hz				
Power Factor	>0.90				
Driver Type	Constant Current				
LED Type	SMD led				
UGR	<19				
Luminous Flux (±10%) 4000k Ra80	3075lm	4610lm	3070lm	4600lm	6070lm
Efficiency (4000k)	> 160lm per watt				
CCT	4000k				
Colour Rendering Index	Ra80				
Beam Angle	90 degrees				
Class	Class II				
IK rating	IK06				
IP Rating	IP44				
Colour	White				
Dimensions	595x595x30mm	595x595x30mm	1195x295x30mm	1195x295x30mm	1195x595x30mm
Options					
Dimmable	Dali, DSI, 1-10v, Triac				
Emergency	Standard, self test, Dali self test				
Sensor	Inbuilt on/off microwave, Dali daylight inbuilt microwave or Remote				
Applications					
Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail					
Accessories					
Surface Mount Frame	PSF600/600BL	PSF600/600BL	PSF1200/300BL	PSF1200/300BL	PSF1200/600BL
Recessed Mount Frame	PRF600/600	PRF600/600	PRF1200/300	PRF1200/300	PRF1200/600
Suspension Kits	SUSKIT/3M (4 wire 3mtr suspension kit)				
	SUSKIT/5M (4 wire 5mtr suspension kit)				
	SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)				
Plasterboard Clips	LEDP/PBC (set of 4)				
Lifespan and Warranty					
Lifetime of LED @ Ta=25°C	> 90,000hrs L80B20				
Warranty	5 years				