

Specification - Com Lite High Efficiency Opal Panel

Revision 1



Product Information			
Model No.	CHL200P/4	CHL4030P/4	
Power Consumption(±5%)	21w	42w	This product can be run at different outputs upon request.
Power Supply	Lifud or European brand on request		
Input Voltage	220-240 VAC, 50-60Hz		
Power Factor	>0.90		
Driver Type	Constant Current		
LED Type	SMD led		
UGR	<22		
Luminous Flux (±10%) 4000k Ra80	4240lm	8205lm	
Efficiency (4000k)	> 190lm per watt	> 195lm per watt	
CCT	4000k		
Colour Rendering Index	Ra80		
Beam Angle	90 degrees		
Class	Class II		
SCDM	< 6		
IK rating	IK06		
IP Rating	IP44		
Colour	White		
Dimensions	595x595x28mm	1195x595x28mm	
Options			
Dimmable	Dali, DSI, 1-10v, Triac		
Emergency	Standard, self test, Dali self test		
Sensor	Inbuilt on/off microwave, Dali daylight inbuilt microwave or Remote		

Applications

Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail



Accessories

Surface Mount Frame	PSF600/600BL	PSF1200/600BL
Recessed Mount Frame	PRF600/600	PRF1200/600
Suspension Kits	SUSKIT/3M (4 wire 3mtr suspension kit)	
	SUSKIT/5M (4 wire 5mtr suspension kit)	
	SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)	
Plasterboard Clips	LEDP/PBC (set of 4)	

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 90,000hrs L80B20
Warranty	5 years