

Specification - Com Lite High Efficiency Opal Panel

Revision 1



Product Information		
Model No.	CHL200P/4	CHL4030P/4
Power Consumption(±5%)	20w	36w
Power Supply	Lifud or European brand on request	
Input Voltage	220-240 VAC, 50-60Hz	
Power Factor	>0.90	
Driver Type	Constant Current	
LED Type	SMD led	
UGR	<22	
Luminous Flux (±10%) 4000k Ra80	4240lm	8205lm
Efficiency (4000k)	> 190lm per watt	> 195lm per watt
CCT	4000k	
Colour Rendering Index	Ra80	
Beam Angle	90 degrees	
Class	Class II	
SCDM	< 6	
IK rating	IK06	
IP Rating	IP44	
Colour	White	
Dimensions	595x595x30mm 1195x595x30mm	

Options	
Dimmable	Dali, DSI, 1-10v, Triac
Emergency	Standard, self test, Dali self test
Sensor	Inbuilt on/off microwave, Dali daylight inbuilt microwave or Remote

Applications

Board Rooms, Corridors, Hotels, Reception Area's, Hospitals, Retail



Accessories

Surface Mount Frame	PSF600/600BL PSF1200/600BL
Recessed Mount Frame	PRF600/600 PRF1200/600
Suspension Kits	SUSKIT/3M (4 wire 3mtr suspension kit) SUSKIT/5M (4 wire 5mtr suspension kit) SUSKIT/BOX (4 wire 2mtr suspension kit with ceiling box)
Plasterboard Clips	LEDP/PBC (set of 4)

Lifespan and Warranty

Lifetime of LED @ Ta=25°C	> 90,000hrs L80B20
Warranty	5 years