

Specification - Com Lite High Efficiency UFO

Revision 1



Product Information			
Model No.	HBO100V2HL	HBO150V2HL	HBO200V2HL
Power Consumption(±5%)	100w	150w	200w
Power Supply	Lifud		
Input Voltage	220-240 VAC, 50-60Hz		
Power Factor	>0.92		
Driver Type	Constant Current		
LED Type	SMD 2835		
Luminous Flux (±10%) 5000k Ra80	18770lm	26265lm	35325lm
Optic	120 degree (90 or 60 degree lens available as option)		
Efficiency (4000k)	> 175lm per watt		
CCT	5000k		
Color Rendering Index	Ra80		
UGR	28		
Class	Class I		
SCDM	< 6		
IK rating	IK08		
IP Rating	IP65		
Colour	RAL9017 (Black)		
Dimensions	290mm diameter x 170mm height	330mm diameter x 170mm height	330mm diameter x 170mm height

Options	
Dimmable	Dali, 1-10v
Emergency	Standard, self test, Dali self test (Remote)
Sensor	Plug in microwave or PIR

Applications

Retail, Sports Courts , Warehouses

Accessories



90 Degree Prismatic Diffuser:
Model HBO/PC



Reflector: Model HBO/AL



Microwave Sensor: 15mtr Height



PIR Sensor: 15mtr Height

Lifespan and Warranty

Lifetime of LED @ Ta=25°C > 80,000hrs L80B20

Warranty 5 years